

# T8V

[ NEW FROM  
ADAM AUDIO ]



**PRE-INFORMATION FOR ADAM AUDIO  
DISTRIBUTORS AND DEALERS ONLY**

THE NEW ADAM AUDIO T8V NEARFIELD MONITOR

 **ADAM AUDIO**

# T8V

NEARFIELD MONITOR

T SERIES

The T8V is an affordable, professional 2-way powered studio monitor with an 8" woofer and ADAM Audio's latest addition to the T Series. Designed around the same technology, features and build quality as its smaller siblings, the T8V provides best-in-class characteristics and sound performance.

The T8V impresses with a multitude of features that bring real benefits to the user: The U-ART tweeter's 4:1 velocity transfer ratio, in combination with the new Class D amplifiers' high dynamic range, yield respective max. peak SPL of 118 dB per pair. The tweeter, which extends up to 25 kHz, works as a team with the HPS Waveguide. This allows an optimal radiation of the high frequencies, which means the advantage of a more controlled, larger usable sweet spot during monitoring. With a bass extension down to 33 Hz, the T8V is especially suitable for users who produce bass-heavy music.

The T8V is the perfect studio speaker for those who have always wanted to work with an 8" monitor from ADAM Audio, but where budgets have been insufficient. The 5-year warranty gives users additional security and the certainty of having purchased a quality product.

**Available in May 2020**



**SRP: 299,00 € incl. VAT**  
**259,00 GBP incl. VAT**  
**\$ 299,00 excl. VAT**

#### Important Information For Logistics:

EAN Code	4260113134238 [EUR]
	4260113134245 [UK]
	4260113134252 [AUS]
	4260113134269 [CN]
	4260113134276 [US]
Dimensions H x W x D including packaging	510 mm x 342 mm x 432 mm [20,1" x 13,5" x 17"]
Weight per unit including packaging	11,8 kg [26 lb]



#### Technical Data:

- U-ART 1.9" Accelerated Ribbon Tweeter
- Polypropylene 8" woofer and rear-firing bass-reflex port
- Max. peak SPL at 1 m per pair: 118 dB
- Built-in Amplifiers: 2 x Class-D
- Amplifier Power U-ART Tweeter: 20 W [RMS]
- Amplifier Power Woofer: 70 W [RMS]
- Frequency Response: 33 Hz – 25 kHz
- Crossover Frequency: 2,6 kHz
- Analog Inputs: XLR, RCA
- H x W x D: 400 mm x 250 mm x 335 mm [15,7" x 9,8" x 13,2"]
- Weight: 9,8 kg [21,6 lb]
- Warranty: 2 years plus 3 years upon product registration in the MyADAM user area



**ADAM AUDIO**

**Full Product Specifications:**

Tweeter	U-ART Tweeter
Woofers	1 x 8" polypropylen woofer, rear ported bass reflex design
Built-in amplifiers	2 x Class-D
Amplifier Power	70 W [Woofer] 20 W [Tweeter]
Input Sensitivity	+4 dBu / -10 dBV
Frequency Response	33 Hz – 25 kHz
Max. SPL at 1 m per pair	118 dB SPL
Crossover Frequency	2,6 kHz
Panel	Rear
Control Options	Level Input switch +/- 2 dB High Shelf and Low Shelf filters
Analog Inputs	1 x XLR female, 1 x RCA female
Power Rating	150 W
Weight	9,8 kg [21.6 lb]
Height x Width x Depth	400 mm x 250 mm x 335 mm [15,7" x 9,8" x 13,2"]
AC Input Voltage	100–240 V multi-range
Warranty period	5 years [2 year parts and labor warranty, plus an additional 3 years available with product registration]
Delivery Contents	Power Cord, Quick Start Guide, Welcome Card

