DECO series



DECO-5-T



DESCRIPTION

The DECO series is a family of ceiling loudspeakers with minimum visual impact thanks to an innovative mechanical design that incorporates grilles attached with powerful neodymium magnets that cover the entire system so that it can blend seamlessly into its environment. All models in the series include loudspeakers with polypropylene cones, making them highly reliable in humid conditions. The design of the rubber mounts provides a high degree of movement and reduces low-frequency distortion levels. All models in the series are white, but black grilles are available as an option when used in spaces with dark ceilings.

The DECO-5T model is a 5" full-range ceiling-mounted acoustic system. It features a 6W 100V line transformer and is specifically designed for high impedance. It is equipped with a 5.25" double cone loudspeaker and a 1" voice coil. A frameless grille design means the system extends just 3 mm from the ceiling, making it practically invisible.

KEY FEATURES

- · 5" ceiling mount loudspeaker
- · 70 Hz 15 kHz bandwidth
- · Multi-tap 70V/100V Transformer
- · Easy mounting system with built-in tabs
- · Frameless grille design with black option

APPLICATIONS

- · Professional Installation Systems
- · Houses of Worship
- · Auditoriums/Theaters
- · Hotel Ballrooms and Meeting Rooms

SPECIFICATIONS

Frequency Range (-10 dB) 70 Hz - 15 kHz Horizontal Coverage (-6 dB) 100° Nominal Impedance 8 ohms Transformer Taps 70 V Tap1, 1.5 W. Tap2, 3 W. Tap3 6 W. Transformer Taps 100 V Tap1, 3 W. Tap2, 6 W. Tap3 X. On-axis Sensitivity 1W/1 m 89 dB SPL Connectors Audio Input Connector Audio Output Connector Spring Terminals Enclosure Enclosure Geometry Color White Cut Out Diameter 169 mm (6,7 in) Depth 75 mm (3,0 in) Dimensions (HxWxD) 205 x 205 x 75 mm 8,0 x 8,0 x 3,0 in Net Weight 0,9 kg (2,0 lb) Shipping Carton Dimensions (HxWxD) 250 x 230 x 370 mm 9,8 x 9,1 x 14,6 in Shipping Weight 1,0 kg (2,2 lb)	Performance		
Nominal Impedance 8 ohms Transformer Taps 70 V Tap1, 1.5 W. Tap2, 3 W. Tap3 6 W. Tap1, 3 W. Tap2, 6 W. Tap3 X. On-axis Sensitivity 1W/1 m 89 dB SPL Connectors Audio Input Connector Spring Terminals Audio Output Connector Spring Terminals Enclosure Enclosure Enclosure Geometry Round Cot Out Diameter 169 mm (6,7 in) Depth 75 mm (3,0 in) Dimensions (H x W x D) 205 x 205 x 75 mm 8,0 x 8,0 x 3,0 in Net Weight 0,9 kg (2,0 lb) Shipping Carton Dimensions (H x W x D) 250 x 230 x 370 mm 9,8 x 9,1 x 14,6 in	Frequency Range (-10 dB)	70 Hz - 15 kHz	
Transformer Taps 70 V Tap1, 1.5 W. Tap2, 3 W. Tap3 6 W. Transformer Taps 100 V Tap1, 3 W. Tap2, 6 W. Tap3 X. On-axis Sensitivity 1W/1 m 89 dB SPL Connectors Audio Input Connector Audio Output Connector Spring Terminals Enclosure Enclosure Geometry Color White Cut Out Diameter 169 mm (6,7 in) Depth 75 mm (3,0 in) Dimensions (H x W x D) 205 x 205 x 75 mm 8,0 x 8,0 x 3,0 in Net Weight 0,9 kg (2,0 lb) Shipping Carton Dimensions (H x W x D) 250 x 230 x 370 mm 9,8 x 9,1 x 14,6 in	Horizontal Coverage (-6 dB)	100°	
Transformer Taps 100 V On-axis Sensitivity 1W/1 m 89 dB SPL Connectors Audio Input Connector Audio Output Connector Spring Terminals Enclosure Enclosure Geometry Color White Cut Out Diameter Depth 75 mm (3,0 in) Dimensions (HxWxD) Net Weight O,9 kg (2,0 lb) Shipping Carton Dimensions (HxWxD) 250 x 230 x 370 mm 9,8 x 9,1 x 14,6 in	Nominal Impedance	8 ohms	
On-axis Sensitivity 1W/1 m 89 dB SPL Connectors Audio Input Connector Spring Terminals Audio Output Connector Spring Terminals Enclosure Enclosure Geometry Round Color White Cut Out Diameter 169 mm (6,7 in) Depth 75 mm (3,0 in) Dimensions (HxWxD) 205 x 205 x 75 mm 8,0 x 8,0 x 3,0 in Net Weight 0,9 kg (2,0 lb) Shipping Carton Dimensions (HxWxD) 250 x 230 x 370 mm 9,8 x 9,1 x 14,6 in	Transformer Taps 70 V	Tap1, 1.5 W. Tap2, 3 W. Tap3 6 W.	
Connectors Audio Input Connector Spring Terminals Audio Output Connector Spring Terminals Enclosure Enclosure Geometry Color White Cut Out Diameter Depth 75 mm (3,0 in) Dimensions (H x W x D) Net Weight Cut Out Diameter 205 x 205 x 75 mm 8,0 x 8,0 x 3,0 in 0,9 kg (2,0 lb) Shipping Carton Dimensions (H x W x D) 250 x 230 x 370 mm 9,8 x 9,1 x 14,6 in	Transformer Taps 100 V	Tap1, 3 W. Tap2, 6 W. Tap3 X.	
Audio Input Connector Spring Terminals Audio Output Connector Spring Terminals Enclosure Round Color White Cut Out Diameter 169 mm (6,7 in) Depth 75 mm (3,0 in) Dimensions (HxWxD) 205 x 205 x 75 mm 8,0 x 8,0 x 3,0 in Net Weight 0,9 kg (2,0 lb) Shipping Carton Dimensions (HxWxD) 250 x 230 x 370 mm 9,8 x 9,1 x 14,6 in	On-axis Sensitivity IW/I m	89 dB SPL	
Audio Input Connector Spring Terminals Audio Output Connector Spring Terminals Enclosure Round Color White Cut Out Diameter 169 mm (6,7 in) Depth 75 mm (3,0 in) Dimensions (HxWxD) 205 x 205 x 75 mm 8,0 x 8,0 x 3,0 in Net Weight 0,9 kg (2,0 lb) Shipping Carton Dimensions (HxWxD) 250 x 230 x 370 mm 9,8 x 9,1 x 14,6 in	Connectors		
Enclosure Round Enclosure Geometry Round Color White Cut Out Diameter 169 mm (6,7 in) Depth 75 mm (3,0 in) Dimensions (H x W x D) 205 x 205 x 75 mm 8,0 x 8,0 x 3,0 in Net Weight 0,9 kg (2,0 lb) Shipping Carton Dimensions (H x W x D) 250 x 230 x 370 mm 9,8 x 9,1 x 14,6 in		Spring Terminals	
Enclosure Round Color White Cut Out Diameter 169 mm (6,7 in) Depth 75 mm (3,0 in) Dimensions (HxWxD) 205 x 205 x 75 mm 8,0 x 8,0 x 3,0 in Net Weight 0,9 kg (2,0 lb) Shipping Carton Dimensions (HxWxD) 250 x 230 x 370 mm 9,8 x 9,1 x 14,6 in	-		
Enclosure Geometry Round Color White Cut Out Diameter 169 mm (6,7 in) Depth 75 mm (3,0 in) Dimensions (H x W x D) 205 x 205 x 75 mm 8,0 x 8,0 x 3,0 in Net Weight 0,9 kg (2,0 lb) Shipping Carton Dimensions (H x W x D) 250 x 230 x 370 mm 9,8 x 9,1 x 14,6 in	Audio Output Connector	Spring Terminals	
Enclosure Geometry Round Color White Cut Out Diameter 169 mm (6,7 in) Depth 75 mm (3,0 in) Dimensions (H x W x D) 205 x 205 x 75 mm 8,0 x 8,0 x 3,0 in Net Weight 0,9 kg (2,0 lb) Shipping Carton Dimensions (H x W x D) 250 x 230 x 370 mm 9,8 x 9,1 x 14,6 in	E. J		
Color White Cut Out Diameter 169 mm (6,7 in) Depth 75 mm (3,0 in) Dimensions (H x W x D) 205 x 205 x 75 mm 8,0 x 8,0 x 3,0 in Net Weight 0,9 kg (2,0 lb) Shipping Carton Dimensions (H x W x D) 250 x 230 x 370 mm 9,8 x 9,1 x 14,6 in	Enclosure		
Cut Out Diameter 169 mm (6,7 in) Depth 75 mm (3,0 in) Dimensions (H x W x D) 205 x 205 x 75 mm 8,0 x 8,0 x 3,0 in Net Weight 0,9 kg (2,0 lb) Shipping Carton Dimensions (H x W x D) 250 x 230 x 370 mm 9,8 x 9,1 x 14,6 in	Enclosure Geometry	Round	
Depth 75 mm (3,0 in) Dimensions (H x W x D) 205 x 205 x 75 mm 8,0 x 8,0 x 3,0 in Net Weight 0,9 kg (2,0 lb) Shipping Carton Dimensions (H x W x D) 250 x 230 x 370 mm 9,8 x 9,1 x 14,6 in	Color	White	
Dimensions (H x W x D) 205 x 205 x 75 mm 8,0 x 8,0 x 3,0 in Net Weight 0,9 kg (2,0 lb) Shipping Carton Dimensions (H x W x D) 250 x 230 x 370 mm 9,8 x 9,1 x 14,6 in	Cut Out Diameter	169 mm (6,7 in)	
Dimensions (H x W x D) 8,0 x 8,0 x 3,0 in Net Weight 0,9 kg (2,0 lb) Shipping 250 x 230 x 370 mm 9,8 x 9,1 x 14,6 in	Depth	75 mm (3,0 in)	
Shipping Carton Dimensions (H x W x D) 250 x 230 x 370 mm 9,8 x 9,1 x 14,6 in	Dimensions (H x W x D)		
Carton Dimensions (H x W x D) 250 x 230 x 370 mm 9,8 x 9,1 x 14,6 in	Net Weight	0,9 kg (2,0 lb)	
	Shipping Weight	1,0 kg (2,2 lb)	



ORDERING INFORMATION

Model	Description	P/N
System		
DECO-5-T		10213201
Accessories		
GR-DC5	Installation & Stacking Acc.	20220500

DIMENSIONS







