



MB 1k

.: MB 1K HANDHELD UNIDIRECTIONAL DYNAMIC VOCAL MICROPHONE :.

A perfect introductory performance mic, the high-output MB 1k is designed for use as a lead, backup, or choral vocal microphone. It features Audio-Technica's Hi-ENERGY® neodymium magnet structure for maximum output and fast transient response, lockable MagnaLock™ switch design for silent on/off operation, and a corrosion-resistant gold-plated XLRM-type connector. The MB 1k is also available in the stage-ready **MB 1k/pack** along with a durable tripod microphone stand that folds for easy transport, a professional Quiet-Flex™ stand clamp for flexible positioning, and a heavy-duty 20' XLR-type cable.

- High-output design for vocals that cut through the mix
- Unidirectional dynamic element design
- Rugged all-metal construction
- Hi-ENERGY® neodymium magnet for improved output and transient response
- Reduced handling noise thanks to anti-shock engineering
- Silent on-off operation thanks to MagnaLock™ switch design
- Corrosion-resistant gold-plated XLRM-type connector
- 5-year microphone warranty

SPECIFICATIONS

ELEMENT	Neodymium Dynamic
POLAR PATTERN	Unidirectional
FREQUENCY RESPONSE	80-12,000 Hz
OPEN CIRCUIT SENSITIVITY	-53 dB (2.2 mV) re 1V at 1 Pa
IMPEDANCE	600 ohms
SWITCH	MagnaLock™ on/off
WEIGHT	11.9 oz (337 g)
DIMENSIONS	7.27" (184.7 mm) long, 2.19" (55.6 mm) head diameter
OUTPUT CONNECTOR	Integral 3-pin gold-plated XLRM-type
ACCESSORIES FURNISHED	AT8470 Quiet-Flex™ stand clamp for 5/8"-27 threaded stands; 5/8"-27 to 3/8"-16 threaded adapter
AUDIO-TECHNICA CASE STYLE	T1

SPECIFICATION GRAPHS

POLAR PATTERN

MB1k & MB1k/c



FREQUENCY RESPONSE

