DECO series



DECO-6-T



DESCRIPTION

The DECO series is a family of ceiling loudspeakers with minimum visual impact thanks to an innovative mechanical design that incorporates grilles attached with powerful neodymium magnets that cover the entire system so that it can blend seamlessly into its environment. All models in the series include loudspeakers with polypropylene cones, making them highly reliable in humid conditions. The design of the rubber mounts provides a high degree of movement and reduces low-frequency distortion levels. All models in the series are white, but black grilles are available as an option when used in spaces with dark ceilings.

The DECO-6T is a wide-range passive two-way ceiling-mounted acoustic system featuring a 6.25" low-frequency cone loudspeaker and a 1" ferrofluid-cooled soft dome tweeter with an integrated diffraction ring. Thanks to the frameless grille design, the system extends just 3 mm from the ceiling, making it practically invisible. It is equipped with a 15W 100V line transformer specifically designed for high impedance.

KEY FEATURES

- · 6" ceiling mount loudspeaker
- · 60 Hz 20 kHz bandwidth
- · Multi-tap 70V/100V transformer
- · Easy mounting system with built-in tabs
- · Frameless grille design with black option

APPLICATIONS

- · Professional Installation Systems
- · Houses of Worship
- · Auditoriums/Theaters
- · Hotel Ballrooms and Meeting Rooms

SPECIFICATIONS

Horizontal Coverage (-6 dB) 95° Nominal Impedance 8 ohms Transformer Taps 70 V Tap1, 2.5 W. Tw.		
Nominal Impedance 8 ohms Transformer Taps 70 V Tap1, 2.5 W. Tw. Transformer Taps 100 V Tap1, 5 W. Ta On-axis Sensitivity IW/I m 90 dB SPL Connectors Audio Input Connector Spring Termi Audio Output Connector Spring Termi Enclosure Enclosure Enclosure Geometry Round Color White Cut Out Diameter 198 mm (7,8 Depth 80 mm (3.2 in Dimensions (HxWxD) 230 x 230 x 8 9,0 x 9,0 x 3,2 Net Weight 1,4 kg (3,1 lb)	60 Hz - 20 kHz	
Transformer Taps 70 V Transformer Taps 100 V Trap1, 5 W. Tap1, 5		
Transformer Taps 70 V W. Transformer Taps 100 V Tap1, 5 W. Ta On-axis Sensitivity 1W/1 m 90 dB SPL Connectors Audio Input Connector Audio Output Connector Spring Termin Enclosure Enclosure Geometry Enclosure Geometry Round Cut Out Diameter 198 mm (7,8 Depth 80 mm (3.2 in Dimensions (HxWxD) 230 x 230 x 8 9,0 x 9,0 x 3,2 Net Weight 1,4 kg (3,1 lb)		
On-axis Sensitivity 1W/1 m 90 dB SPL Connectors Audio Input Connector Spring Termi Audio Output Connector Enclosure Enclosure Geometry Round Color White Cut Out Diameter Depth Dimensions (HxWxD) 230 x 230 x 8 9,0 x 9,0 x 3,2 Net Weight 1,4 kg (3,1 lb)	ap2, 5 W. Tap3 7.5	
Connectors Audio Input Connector Spring Termi Audio Output Connector Spring Termi Enclosure Enclosure Geometry Round Color White Cut Out Diameter 198 mm (7,8 Depth 80 mm (3,2 in 19,0 x 9,0 x	p2, 10 W. Tap3 15 W.	
Audio Input Connector Spring Termi Audio Output Connector Enclosure Enclosure Geometry Round Color White Cut Out Diameter Depth Dimensions (HxWxD) 230 x 230 x 8 9,0 x 9,0 x 3,2 Net Weight Net Weight		
Audio Input Connector Spring Terminal Audio Output Connector Spring Terminal Enclosure Round Color White Cut Out Diameter 198 mm (7,8 Depth 80 mm (3,2 in price of the second		
Enclosure Round Enclosure Geometry Round Color White Cut Out Diameter 198 mm (7,8 Depth 80 mm (3,2 in processing to processing the processing to processing the processing that the processing the processing the processing the processing the processing the processing that the processing the proc	inals	
Enclosure Geometry Round Color White Cut Out Diameter 198 mm (7,8 Depth 80 mm (3.2 in page 2) Dimensions (H x W x D) 230 x 230 x 8 9,0 x 9,0 x 3,2 Net Weight 1,4 kg (3,1 lb)	nals	
Color White Cut Out Diameter 198 mm (7,8 Depth 80 mm (3,2 in part of the state o		
Cut Out Diameter 198 mm (7,8 Depth 80 mm (3,2 in the second s		
Depth 80 mm (3,2 ii Dimensions (H x W x D) 230 x 230 x 8 9,0 x 9,0 x 3,2 Net Weight 1,4 kg (3,1 lb)		
Dimensions (H x W x D) 230 x 230 x 8 9,0 x 9,0 x 3,2 Net Weight 1,4 kg (3,1 lb)	in)	
Net Weight 9,0 x 9,0 x 3,2 Net Weight 1,4 kg (3,1 lb)	n)	
Shipping		
Carton Dimensions (H x W x D) 270 x 250 x 3 10,6 x 9,8 x 15		
Shipping Weight 1,5 kg (3,3 lb)	



ORDERING INFORMATION

Model	Description	P/N
System		
DECO-6-T		10213203
Accessories		
GR-DC6	Installation & Stacking Acc.	20220501

DIMENSIONS







